	<u> </u> 46	1st REVISED	PAGE		
TARIFF NO. 010		EFFECTIVE:	FEBRUARY 5, 2000		
SECTION ELEVEN GENERAL INFORMATION	FMC SUBRULE: 34-	G01			
FOR EXPLANATION OF SYMBOLS, SEE PAGE 0-A (AFTER TITLE PAGE)					

FOR EXPLANATION OF SYMBOLS, SEE PAGE 0-A (AFTER TITLE PAGE)					
The Port of Miami-Dade, under continuing construction on the Dodge and Lummus Island sites south of the main channel opposite MacArthur Causeway, is being built on 525 acres. Current improvements are described as follows:		ITEM			
Marginal Berthing 6,700 feet along the north side with 36 feet of water at MLW.					
3,400 feet along the southeast side of Lummus Island and Fisherman's Channel with 42 feet depth of MLW at the gantry crane facility.	DESCRIPTION (C)	850			
Two berths, 400 and 450 feet in the south slip separating Dodge and Lummus Islands with 25 feet of water at MLW is approached from Fisherman's Channel.					
700 feet along the south side at the south east corner of Dodge Island and with 25 feet of water at MLW.					
One berth at northwest section - 750 feet long with 32 feet.					
1,450 feet west of the NOAA slip in Fisherman's Channel with a 25 feet depth at MLW.					
1,390 feet at the west end of Fisherman's Channel with a depth of 25 feet MLW.					
Width of Apron					
70 to 100 feet, north side					
50 to 100 feet, east side 50 to 100 feet, south side					
50 to 100 feet, west side					
Apron Above MLW					
7.5 feet on all sides					

	<u>46</u>	1st REVISED	PAGE		
TARIFF NO. 010					
		EFFECTIVE:	FEBRUARY 5, 2000		
SECTION ELEVEN					
GENERAL INFORMATION					
FMC SUBRULE: 34-G01					
FOR EYPLANATION OF SYMBOLS, SEE DAGE 0-A (AFTER TITLE DAGE)					